



Printing date 04.03.2025 Version number 305 (replaces version 304) Revision: 04.03.2025

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier 600002

· Trade name: Drilling and Cutting Oil Spray E-COLL

· Article number: 4317784464895

· UFI: 1SXQ-M4RY-EC05-E546

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumersSU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the mixture Lubricant
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number:

Poison Control Center Mainz - 24 hour emergency service - phone: +49 (0) 6131/19240

#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







Version number 305 (replaces version 304) Revision: 04.03.2025 Printing date 04.03.2025

Trade name: Drilling and Cutting Oil Spray E-COLL

(Contd. of page 1)

· Signal word Danger

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

P211 Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use. P251

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501

Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

#### · 2.3 Other hazards

#### · Results of PBT and vPvB assessment

· **PBT:** Not applicable. vPvB: Not applicable.

**SECTION 3: Composition/information on ingredients** 

#### · 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

#### Dangerous components:

CAS: 115-10-6 dimethyl ether 🏵 Flam. Gas 1A, H220 Acute Tox. 2, H330 EINECS: 204-065-8 Press. Gas (Comp.), H280 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37-xxxx

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

#### · 4.1 Description of first aid measures

· After inhalation: Supply fresh air.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

#### · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 3)

30-50%





Printing date 04.03.2025 Version number 305 (replaces version 304) Revision: 04.03.2025

Trade name: Drilling and Cutting Oil Spray E-COLL

(Contd. of page 2)

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents:
   CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Do not inhale explosion gases or combustion gases.
- · Additional information Cool endangered receptacles with water spray.

#### **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures
  Wear protective equipment. Keep unprotected persons away.
  Ensure adequate ventilation
- · 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

- · 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling Use only in well ventilated areas.

(Contd. on page 4)





Printing date 04.03.2025 Version number 305 (replaces version 304) Revision: 04.03.2025

Trade name: Drilling and Cutting Oil Spray E-COLL

(Contd. of page 3)

· Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Do not spray onto a naked flame or any incandescent material.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

- 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

CAS: 115-10-6 dimethyl ether

IOELV Long-term value: 1920 mg/m³, 1000 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- $\cdot$  Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection: Not necessary if room is well-ventilated.
- · Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several

(Contd. on page 5)





Printing date 04.03.2025 Version number 305 (replaces version 304) Revision: 04.03.2025

Trade name: Drilling and Cutting Oil Spray E-COLL

(Contd. of page 4)

substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

· Body protection: Protective work clothing

#### **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties

· General Information

Colour:
Odour:
Odour threshold:
Melting point/freezing point:

Light yellow
Characteristic
Not determined.
Undetermined.

· Boiling point or initial boiling point and boiling

range Not applicable, as aerosol.

· Flammability Not applicable.

· Lower and upper explosion limit

Lower: 3 Vol %
 Upper: 18.6 Vol %
 Flash point: -41 °C
 Auto-ignition temperature: 235 °C

Decomposition temperature:
 pH
 Not determined.
 Not determined.

· Viscosity:

· **Kinematic viscosity** Not determined.

· Kinematic: 23 °C - 4 mm (ISO 2431)

· **Dynamic:** Not determined.

· Solubility

· water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value)
 Vapour pressure at 20 °C:
 Not determined.
 5,000 hPa

· Density and/or relative density

Density at 20 °C: 0.78 g/cm³
 Relative density Not determined.
 Vapour density Not determined.

(Contd. on page 6)





Printing date 04.03.2025 Version number 305 (replaces version 304) Revision: 04.03.2025

Trade name: Drilling and Cutting Oil Spray E-COLL

(Contd. of page 5)

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health and environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent separation test:

• Organic solvents: 50.0 % 50 % • VOC (EC) % 50.00 %

· VOC (EC) g/l

· VOCV (CH) 50.00 %

· Change in condition

· Drip point:

Oxidising propertiesEvaporation rateNot determined.Not applicable.

· Information with regard to physical hazard

classes

Explosives VoidFlammable gases Void

• Aerosols Extremely flammable aerosol. Pressurised container:

May burst if heated.

 Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void Void · Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void

#### **SECTION 10: Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

(Contd. on page 7)





Printing date 04.03.2025 Version number 305 (replaces version 304) Revision: 04.03.2025

Trade name: Drilling and Cutting Oil Spray E-COLL

(Contd. of page 6)

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
   No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

#### **SECTION 11: Toxicological information**

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

CAS: 115-10-6 dimethyl ether

Inhalative LC50/4h 308 ppm (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.





Printing date 04.03.2025 Version number 305 (replaces version 304) Revision: 04.03.2025

Trade name: Drilling and Cutting Oil Spray E-COLL

(Contd. of page 7)

#### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Harmful to aquatic organisms

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

#### **SECTION 13: Disposal considerations**

#### · 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

#### · European waste catalogue

16 05 04\* gases in pressure containers (including halons) containing hazardous substances

15 01 10\* packaging containing residues of or contaminated by hazardous substances

#### **SECTION 14: Transport information**

- · 14.1 UN number or ID number
- · ADR, IMDG, IATA UN1950
- · 14.2 UN proper shipping name
- · ADR UN1950 AEROSOLS

(Contd. on page 9)





Printing date 04.03.2025 Version number 305 (replaces version 304) Revision: 04.03.2025

Trade name: Drilling and Cutting Oil Spray E-COLL

(Contd. of page 8)

· IMDG AEROSOLS

· IATA AEROSOLS, flammable

· 14.3 Transport hazard class(es)

· ADR



· Class 2 5F Gases.

· Label 2.1

· IMDG, IATA



· Class 2.1 Gases.

· Label 2.1

· 14.4 Packing group

· IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Gases.

· Hazard identification number (Kemler code):

• **EMS Number**: F-D,S-U

· 14.7 Maritime transport in bulk according to IMO

**instruments** Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 1L

• Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

Transport categoryTunnel restriction code

·IMDG

Limited quantities (LQ)Excepted quantities (EQ)Code: E0

Not permitted as Excepted Quantity

· UN "Model Regulation": UN1950, AEROSOLS, 2.1

EU-





Printing date 04.03.2025 Version number 305 (replaces version 304) Revision: 04.03.2025

Trade name: Drilling and Cutting Oil Spray E-COLL

(Contd. of page 9)

#### **SECTION 15: Regulatory information**

- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



- · Signal word Danger
- · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Chemical safety assessment
- · Named dangerous substances ANNEX I Methanol
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

(Contd. on page 11)





Version number 305 (replaces version 304) Printing date 04.03.2025 Revision: 04.03.2025

Trade name: Drilling and Cutting Oil Spray E-COLL

(Contd. of page 10)

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H330 Fatal if inhaled.

· Department issuing SDS: Product safety department

· Contact: sdb@ede.de

· Date of previous version: 02.07.2022 · Version number of previous version: 304

#### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Acute Tox. 2: Acute toxicity - Category 2

· \* Data compared to the previous version altered.