



Printing date 22.04.2025 Version number 301 Revision: 22.04.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier 600499

· Trade name: Grundierspray grau

· Article number: 4317784612357

· UFI: 2DJ2-XCW8-Y80X-3XGV

1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the mixture Coating
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number:

Poison Control Center Mainz - 24 hour emergency service - phone: +49 (0) 6131/19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)





Printing date 22.04.2025 Version number 301 Revision: 22.04.2025

Trade name: Grundierspray grau

(Contd. of page 1)

· Hazard pictograms





GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

n-butyl acetate acetone ethyl acetate

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves / eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

EUH018 In use may form flammable/explosive vapour-air mixture.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

The product does not meet the PBT and vPvB classification criteria

Contains no PBT and/or vPvB substances ≥ 0.1%, assessed according to REACH Annex XIII

· PBT: Not applicable.

· vPvB: Not applicable.





Printing date 22.04.2025 Version number 301 Revision: 22.04.2025

Trade name: Grundierspray grau

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29-xxxx 01-2119485493-29-0059	n-butyl acetate Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	10-50%	
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane, pure Flam. Gas 1A, H220 Press. Gas (Comp.), H280	10-<25%	
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49-xxxx 01-2119498062-37-xxxx	acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	2.5-<25%	
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	2.5-10%	
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46-xxxx	ethyl acetate Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	2.5-10%	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information: Personal protection for the First Aider.

· After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 4)





Printing date 22.04.2025 Version number 301 Revision: 22.04.2025

Trade name: Grundierspray grau

(Contd. of page 3)

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.
- · 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Mouth respiratory protective device.

· Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow product to reach sewage system or any water course.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 5)





Printing date 22.04.2025 Version number 301 Revision: 22.04.2025

Trade name: Grundierspray grau

(Contd. of page 4)

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Use only in well ventilated areas.
- · Information about fire and explosion protection:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from oxidising agents.
- Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

CAS: 123-86-4 n-butyl acetate

IOELV Short-term value: 723 mg/m³, 150 ppm

Long-term value: 241 mg/m³, 50 ppm

CAS: 67-64-1 acetone

IOELV Long-term value: 1210 mg/m³, 500 ppm

CAS: 141-78-6 ethyl acetate

IOELV Short-term value: 1468 mg/m³, 400 ppm

Long-term value: 734 mg/m³, 200 ppm

· Additional information: The lists valid during the making were used as basis.

(Contd. on page 6)





Printing date 22.04.2025 Version number 301 Revision: 22.04.2025

Trade name: Grundierspray grau

(Contd. of page 5)

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- · Respiratory protection: Self-contained respiratory protective device.
- Hand protection



Protective gloves

· Material of gloves

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

Physical stateColour:Aerosol Grey

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range Not applicable, as aerosol.Flammability Extremely flammable aerosol.

(Contd. on page 7)





Printing date 22.04.2025 Version number 301 Revision: 22.04.2025

Trade name: Grundierspray grau

(Contd. of page 6)

· Lower and upper explosion limit

• **Lower**: 1.4 Vol % • **Upper**: 15 Vol %

· Flash point: Not applicable, as aerosol.

Auto-ignition temperature: >200 °C
 Decomposition temperature: Not determined.
 pH Not determined.

· Viscosity:

· **Kinematic viscosity** Not determined.

· Kinematic: 23 °C - 4 mm (ISO 2431)

• **Dynamic:** Not determined.

Solubility

• water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value)
 Vapour pressure at 20 °C:
 4,200 hPa

Density and/or relative density

Density at 20 °C: 0.71 g/cm³
 Relative density Not determined.
 Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health

and environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

· Explosive properties: Not determined.

· Solvent separation test:

Organic solvents: 66.0 %
 VOC (EC) % 62.50 %
 VOC (EC) g/I 665.0 g/I

· Change in condition

• Evaporation rate Not applicable.

· Information with regard to physical hazard

classes

Explosives VoidFlammable gases Void

• Aerosols Extremely flammable aerosol. Pressurised container:

May burst if heated.

Void · Oxidising gases · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable

gases in contact with water Void

Oxidising liquids
 Void

(Contd. on page 8)





Printing date 22.04.2025 Version number 301 Revision: 22.04.2025

Trade name: Grundierspray grau

(Contd. of page 7)

· Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void Void · Desensitised explosives

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
CAS: 123-	CAS: 123-86-4 n-butyl acetate		
Oral	LD50	13,100 mg/kg (rat)	
Dermal	LD50	>5,000 mg/kg (rabbit)	
Inhalative	LC50/4h	>21 ppm (rat)	
CAS: 106-97-8 butane, pure			
Inhalative	LC50/4h	658 ppm (rat)	
CAS: 67-64-1 acetone			
Oral	LD50	5,800 mg/kg (rat)	
Dermal	LD50	20,000 mg/kg (rabbit)	
Inhalative	LC50/4h	76 mg/m³ (rat)	
CAS: 74-9	CAS: 74-98-6 propane		
Inhalative	LC50/4h	>20 mg/m³ (rat)	
CAS: 141-78-6 ethyl acetate			
Oral	LD50	5,620 mg/kg (rabbit)	
Inhalative	LC50/4h	1,600 ppm (rat)	
	•	(Contd. on page 9)	





Printing date 22.04.2025 Version number 301 Revision: 22.04.2025

Trade name: Grundierspray grau

(Contd. of page 8)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:		
CAS: 123-86-4 n-butyl acetate		
LC50 (96h)	18 mg/L (Pimephales promelas)	
EC50 (48h)	44 mg/L (Daphnia magna)	
EC50/24h	73 mg/l (Daphnia magna)	
EC50/72h	647.7 mg/l (S)	
CAS: 67-64-1 acetone		
LC50 (96h)	5,000 mg/L (Lepomis macrochirus)	
LC50/48h	8,800 mg/l (Daphnia magna)	
NOEC	430 mg/l (algae)	
NOEC/16h	1,700 mg/l (Pseudomonas putida)	
NOEC/48h	4,740 mg/l (Pseudokirchneriella subcapitata)	
96h LC50	5,540 mg/l (Oncorhynchus mykiss)	

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.





Printing date 22.04.2025 Version number 301 Revision: 22.04.2025

Trade name: Grundierspray grau

(Contd. of page 9)

· 12.5 Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

· 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Harmful to aquatic organisms

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

· European	· European waste catalogue		
-	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS		
08 01 00	wastes from MFSU and removal of paint and varnish		
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances		
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED		
15 01 00	packaging (including separately collected municipal packaging waste)		
15 01 04	metallic packaging		
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED		
15 01 00	packaging (including separately collected municipal packaging waste)		
15 01 11*	metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers		
HP3	Flammable		
HP4	Irritant - skin irritation and eye damage		
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity		

EU -





Printing date 22.04.2025 Version number 301 Revision: 22.04.2025

Trade name: Grundierspray grau

(Contd. of page 10)

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR UN1950 AEROSOLS

· IMDG, IATA AEROSOLS

· 14.3 Transport hazard class(es)

· ADR



· Class 2 5F Gases.

· Label 2.1

· IMDG, IATA



Class
 Label
 2 Gases.
 2.1

· 14.4 Packing group

· ADR Void

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Gases.

· Hazard identification number (Kemler code): 2.1

• Stowage Code SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS:

Category C, Clear of living quarters.

(Contd. on page 12)





Revision: 22.04.2025 Printing date 22.04.2025 Version number 301

Trade name: Grundierspray grau

(Contd. of page 11)

· Segregation Code SG69 For AEROSOLS with a maximum capacity of 1

Segregation as for class 9. Stow "separated from"

class 1 except for division 1.4.

For AEROSOLS with a capacity above 1 litre:

Segregation as for the appropriate subdivision of class

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class

· 14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

Transport/Additional information:

· ADR

· Limited quantities (LQ) 1L

· Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· Transport category D

· Tunnel restriction code

· IMDG

· Limited quantities (LQ) 1L

· Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· UN "Model Regulation": UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

n-butyl acetate acetone ethyl acetate

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.





Printing date 22.04.2025 Version number 301 Revision: 22.04.2025

Trade name: Grundierspray grau

(Contd. of page 12)

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves / eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Chemical safety assessment
- · Named dangerous substances ANNEX I Methanol
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

CAS: 67-64-1 acetone

· Regulation (EC) No 273/2004 on drug precursors

CAS: 67-64-1 acetone

 Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

CAS: 67-64-1 acetone

3

- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

· Exposure scenario(s)

Exposure scenario(s) of ingredients (if present) are available on request at:

(Contd. on page 14)





Printing date 22.04.2025 Version number 301 Revision: 22.04.2025

Trade name: Grundierspray grau

(Contd. of page 13)

sdb@ede.de

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing SDS: Product safety department

· Contact: sdb@ede.de

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

EU -