



Printing date 22.04.2025 Version number 311 (replaces version 310) Revision: 22.04.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier 600077

· Trade name: Zinc-aluminium spray E-COLL

· Article number: 4317784349161

· UFI: SXYX-JQ8C-390R-02FE

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the mixture Anticorrosion additive
- · 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number:

Poison Control Center Mainz - 24 hour emergency service - phone: +49 (0) 6131/19240

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The labelling of an aspiration hazard (Asp.Tox.1 H304) is not required for aerosol dispensers and containers with a sealed spray device (Regulation (EC) 1272/2008, Annex 1,1.3.3). The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)





Printing date 22.04.2025 Version number 311 (replaces version 310) Revision: 22.04.2025

Trade name: Zinc-aluminium spray E-COLL

(Contd. of page 1)

· Hazard pictograms





GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

acetone

ethyl acetate

Solvent naphtha (petroleum), light arom.

Hydrocarbons, C9-C11, n-alcanes, isoalcanes, aromatics (<2%)

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

The product does not meet the PBT and vPvB classification criteria Contains no PBT and/or vPvB substances ≥ 0.1%, assessed according to REACH Annex XIII

- · PBT: Not applicable.
- · vPvB: Not applicable.





Printing date 22.04.2025 Version number 311 (replaces version 310) Revision: 22.04.2025

Trade name: Zinc-aluminium spray E-COLL

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:				
	It. dans a muse	05 5001		
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane, pure Tress. Gas 1A, H220 Press. Gas (Comp.), H280	25-<50%		
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49-xxxx 01-2119498062-37-xxxx	acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	10-<25%		
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	10-<25%		
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46-xxxx		10-<25%		
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32-xxxx	xylene ♠ Flam. Liq. 3, H226 ♠ Asp. Tox. 1, H304 ♠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	<1.25%		
CAS: 7429-90-5 EINECS: 231-072-3 Index number: 013-002-00-1 Reg.nr.: 01-2119529243-45	aluminium powder (stabilised) Flam. Sol. 1, H228	1-<5%		
CAS: 7440-66-6 EINECS: 231-175-3 Index number: 030-001-01-9 Reg.nr.: 01-2119467174-37	zinc powder -zinc dust (stabilized) Aquatic Acute 1, H400; Aquatic Chronic 1, H410	1-<5%		
CAS: 64742-95-6 EC number: 918-668-5 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35-xxxx 01-2119487492-29- XXXX	Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335-H336	1-<5%		
EC number: 919-857-5 Index number: 649-327-00-6 Reg.nr.: 01-2119463258-33-xxxx	Asp. Tox. 1, H304 STOT SE 3, H336 EUH066	1-<5%		





Printing date 22.04.2025 Version number 311 (replaces version 310) Revision: 22.04.2025

Trade name: Zinc-aluminium spray E-COLL

(Contd. of page 3)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.
- · 5.3 Advice for firefighters
- · Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

· Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures
 Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

(Contd. on page 5)





Printing date 22.04.2025 Version number 311 (replaces version 310) Revision: 22.04.2025

Trade name: Zinc-aluminium spray E-COLL

(Contd. of page 4)

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Open and handle receptacle with care. Use only in well ventilated areas.

· Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- Information about storage in one common storage facility: Store away from oxidising agents.
- Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

CAS: 67-64-1 acetone

IOELV Long-term value: 1210 mg/m³, 500 ppm

(Contd. on page 6)





Printing date 22.04.2025 Version number 311 (replaces version 310) Revision: 22.04.2025

Trade name: Zinc-aluminium spray E-COLL

(Contd. of page 5)

CAS: 141-78-6 ethyl acetate

IOELV Short-term value: 1468 mg/m³, 400 ppm Long-term value: 734 mg/m³, 200 ppm

CAS: 1330-20-7 xylene

IOELV Short-term value: 442 mg/m³, 100 ppm Long-term value: 221 mg/m³, 50 ppm

Skin

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

· Respiratory protection:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

Self-contained respiratory protective device.

· Hand protection



Protective gloves

· Material of gloves

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

· Body protection: Solvent resistant protective clothing





Version number 311 (replaces version 310) Revision: 22.04.2025 Printing date 22.04.2025

Trade name: Zinc-aluminium spray E-COLL

(Contd. of page 6)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Aerosol · Colour: Grey

· Odour: Characteristic · Odour threshold: Not determined.

· Melting point/freezing point: -187 °C

· Boiling point or initial boiling point and boiling

range Not applicable, as aerosol.

· Flammability Extremely flammable aerosol.

The mixture is capable of catching fire or being set on

The substance is capable of catching fire or being set

on fire.

· Lower and upper explosion limit

· Lower: 1.1 Vol % · Upper: 15 Vol %

· Flash point: Not applicable, as aerosol.

· Auto-ignition temperature: >200 °C · Decomposition temperature: Not determined. · pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined.

· Kinematic: 23 °C - 4 mm (ISO 2431)

· Dynamic: Not determined.

· Solubility

Not miscible or difficult to mix. · water:

· Partition coefficient n-octanol/water (log value) Not determined. 7,400 hPa

Vapour pressure at 20 °C:

· Density and/or relative density

· Density at 20 °C: 0.6809 g/cm³ Relative density Not determined. · Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health

and environment, and on safety.

· Ignition temperature: Product is not selfigniting.

· Explosive properties: Not determined.

· Solvent separation test:

· VOC (EC) % 95.50 % · VOC (EC) g/l 655.2 g/l

· Change in condition

· Drip point:

· Oxidising properties Not determined.

(Contd. on page 8)





Printing date 22.04.2025 Version number 311 (replaces version 310) Revision: 22.04.2025

Trade name: Zinc-aluminium spray E-COLL

(Contd. of page 7)

· Information with regard to physical hazard

classes

· Evaporation rate

• Explosives Void Void
• Flammable gases Void

• Aerosols Extremely flammable aerosol. Pressurised container:

Void

May burst if heated.

Not applicable.

· Oxidising gases
Void
Void
· Gases under pressure
Void
· Flammable liquids
Void
Void
Void

· Flammable solids Void Void

· Self-reactive substances and mixtures Void Void

· Pyrophoric liquids Void

Pyrophoric solidsVoidVoid

· Self-heating substances and mixtures Void Void

 Substances and mixtures, which emit flammable gases in contact with water

Void

Void
Oxidising liquids

Void • Oxidising solids Void

Void
• Organic peroxides

Void

Void
Corrosive to metals
Void
Void

· Desensitised explosives Void Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 9)





Printing date 22.04.2025 Version number 311 (replaces version 310) Revision: 22.04.2025

Trade name: Zinc-aluminium spray E-COLL

(Contd. of page 8)

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 v	· LD/LC50 values relevant for classification:				
CAS: 106-97-8 butane, pure					
Inhalative	LC50/4h	658 ppm (rat)			
CAS: 67-6	CAS: 67-64-1 acetone				
Oral	LD50	5,800 mg/kg (rat)			
Dermal	LD50	20,000 mg/kg (rabbit)			
		76 mg/m³ (rat)			
CAS: 74-98-6 propane					
		>20 mg/m³ (rat)			
	CAS: 141-78-6 ethyl acetate				
Oral	LD50	5,620 mg/kg (rabbit)			
		1,600 ppm (rat)			
	CAS: 1330-20-7 xylene				
Dermal	LD50	1,100 mg/kg (rabbit)			
Inhalative	LC50/4h	11 mg/m³ (rat)			
	CAS: 64742-95-6 Solvent naphtha (petroleum), light arom.				
Oral	LD50	>6,800 mg/kg (rat)			
Dermal	LD50	>3,400 mg/kg (rab)			
		>10.2 ppm (rat)			
Hydrocarbons, C9-C11, n-alcanes, isoalcanes, aromatics (<2%)					
Oral	LD50	>15,000 mg/kg (rat) (OECD 401)			
Dermal	LD50	3,400 mg/kg (rat) (OECD 402)			
Inhalative	LC50/4h	13,100 ppm (rat) (OECD 403)			

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.





Printing date 22.04.2025 Version number 311 (replaces version 310) Revision: 22.04.2025

Trade name: Zinc-aluminium spray E-COLL

(Contd. of page 9)

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:			
CAS: 67-64-1 acetone			
LC50 (96h)	5,000 mg/L (Lepomis macrochirus)		
LC50/48h	8,800 mg/l (Daphnia magna)		
NOEC	430 mg/l (algae)		
NOEC/16h	1,700 mg/l (Pseudomonas putida)		
NOEC/48h	4,740 mg/l (Pseudokirchneriella subcapitata)		
96h LC50	5,540 mg/l (Oncorhynchus mykiss)		
Hydrocarbons, C9-C11, n-alcanes, isoalcanes, aromatics (<2%)			
NOEC	24.3 mg/l (rat)		

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB**: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

(Contd. on page 11)





Printing date 22.04.2025 Version number 311 (replaces version 310) Revision: 22.04.2025

Trade name: Zinc-aluminium spray E-COLL

(Contd. of page 10)

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods:
- · European waste catalogue

16 05 04* gases in pressure containers (including halons) containing hazardous substances

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR UN1950 AEROSOLS

· IMDG AEROSOLS

· IATA AEROSOLS, flammable

· 14.3 Transport hazard class(es)

· ADR



· Class 2 5F Gases.

· Label 2.1

· IMDG, IATA



Class
 Label
 2 Gases.
 2.1

(Contd. on page 12)





Printing date 22.04.2025 Version number 311 (replaces version 310) Revision: 22.04.2025

Trade name: Zinc-aluminium spray E-COLL

(Contd. of page 11)

· 14.4 Packing group

· ADR Void

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Gases.

• EMS Number: F-D,S-U

· Stowage Code SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS:

Category C, Clear of living quarters.

Segregation Code
 SG69 For AEROSOLS with a maximum capacity of 1

litre:

Segregation as for class 9. Stow "separated from"

class 1 except for division 1.4.

For AEROSOLS with a capacity above 1 litre:

Segregation as for the appropriate subdivision of class

2.

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class

2.

· 14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 1L

• Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

• Transport category 2

• Transport category 2
• Tunnel restriction code D

· IMDG

Limited quantities (LQ)Excepted quantities (EQ)Code: E0

Not permitted as Excepted Quantity

· UN "Model Regulation": UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 13)





Printing date 22.04.2025 Version number 311 (replaces version 310) Revision: 22.04.2025

Trade name: Zinc-aluminium spray E-COLL

(Contd. of page 12)

· Hazard pictograms





GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

acetone

ethyl acetate

Solvent naphtha (petroleum), light arom.

Hydrocarbons, C9-C11, n-alcanes, isoalcanes, aromatics (<2%)

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- Chemical safety assessment
- · Named dangerous substances ANNEX I Methanol
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

(Contd. on page 14)





Version number 311 (replaces version 310) Revision: 22.04.2025 Printing date 22.04.2025

Trade name: Zinc-aluminium spray E-COLL

(Contd. of p	age 13)	
· Annex II - REPORTABLE EXPLOSIVES PRECURSORS		
CAS: 67-64-1 acetone		
· Regulation (EC) No 273/2004 on drug precursors		
CAS: 67-64-1 acetone	3	
 Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors 		
CAS: 67-64-1 acetone	3	

National regulations:

· Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

Exposure scenario(s)

Exposure scenario(s) of ingredients (if present) are available on request at: sdb@ede.de

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220	Extremely flammable gas.
	Extromoty mammable gae.

Highly flammable liquid and vapour. H225

Flammable liquid and vapour. H226

H228 Flammable solid.

H280 Contains gas under pressure; may explode if heated.

May be fatal if swallowed and enters airways. H304

H312 Harmful in contact with skin.

Causes skin irritation. H315

Causes serious eye irritation. H319

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

May cause drowsiness or dizziness. H336

Very toxic to aquatic life. H400

H410 Very toxic to aquatic life with long lasting effects.

Toxic to aquatic life with long lasting effects. H411

EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing SDS: Product safety department

· Contact: sdb@ede.de

· Date of previous version: 19.11.2020 · Version number of previous version: 310

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals





Printing date 22.04.2025 Version number 311 (replaces version 310) Revision: 22.04.2025

Trade name: Zinc-aluminium spray E-COLL

(Contd. of page 14)

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Flam. Sol. 1: Flammable solids - Category 1 Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

EU -

^{· *} Data compared to the previous version altered.